

Home Audio Loudspeaker System



Front row seats to the concert, now available.

The JBL Stage is an advanced, home-stereo/home-theater speaker system that offers you the thrill of a live-concert experience, all in your living room. Featuring 1" aluminum dome tweeters with high-defi nition waveguide sound design and 8" woofers that register deep, signature JBL bass, the JBL Stage captures every note of the audio spectrum from high to low — and combines them into pure listening pleasure. Available in pantone black or two-tone wood, JBL Stage is a stylish addition to any theater system. Whether it's for movies or music, the sound of your home will never be the same.

Features

- ► Two-tone unique design for wood
- ➤ JBL engineering high-defi nition imaging waveguide design and 1" aluminum dome tweeters
- ► Long excursion powered subwoofer



Home Audio Loudspeaker System

Features and Benefits

Two-tone unique design for wood

Enjoy all your music and movies with rich, realistic audio.

JBL engineering high-definition imaging waveguide design and 1" aluminum dome tweeters

Ensures sound quality that's rich, lively, and accurate to a fault.

Long excursion powered subwoofer

The long excursion powered subwoofer provides powerful, quality bass.

What's in the box:

STAGE A190

- 1 x JBL Stage A190 Floor Standing
- 1 x Owner's Manua
- 1 x Warranty Card
- 4 x Outriggers
- 8 x Screws for Outriggers
- 4 x Floor Spikes
- 4 x Rubber Feet

STAGE A180

- 1 x JBL Stage A180 Floor Standing
- Loudspeaker
- 1 x Owner's Manual
- 1 x Warranty Card
- 4 x Outriggers
- 8 x Screws for Outriggers
- 4 x Floor Spikes
- 4 x Rubber Feet

STAGE A170

- 1 x JBL Stage A170 Floor Standing
- Loudspeake
- 1 x Owner's Manual
- 1 x Warranty Card
- 4 x Outriggers
- 8 x Screws for Outriggers
- 4 x Floor Spikes
- 4 x Rubber Feet

STAGE A130

- 2 x JBL Stage A130 Bookshelf
- Loudspeaker
- 1 x Owner's Manual
- 1 x Warranty Card
- 8 x Feet Pads

STAGE A120

- 2 x JBL Stage A120 Compact
- Bookshelf Loudspeaker
- 1 x Owner's Manual
- 1 x Warranty Card
- 8 x Feet Pads
- 2 x Foam Plugs
- 4 x Wall Brackets
- 8 x Screws for Wall Brackets

STAGE A135C

- 1 x JBL Stage A135C Center
- Loudspeake
- 1 x Owner's Manual
- 1 x Warranty Card
- 4 x Feet Pads
- 4 x Metal Levelling Feet

STAGE A125C

- 1 x JBL Stage A125C Compact
- Centei
- Loudspeaker
- 1 x Owner's Manual
- 1 x Warranty Card
- 4 x Feet Pads
- 4 x Metal Levelling Feet

STAGE A120P

- 1 x JBL Stage A120P 500 Watts
- Powered
- Subwoofer
- 1 x Power Cord
- 1 x Owner's Manual
- 1 x Warranty Card
- 1 x Safety Sheet
- 4 x Floor Spikes

STAGE A100P

- 1 x JBL Stage A100P 300 Watts
- Powered
- Subwoofer
- 1 x Power Cord
- 1 x Owner's Manual
- 1 x Warranty Card
- 1 x Safety Sheet
- 4 x Floor Spikes
- Home Audio Loudspeaker System



Home Audio Loudspeaker System

Technical Specifications:

STAGE A190

2.5 way, dual 8", 1" aluminum tweeter floor standing loudspeaker

2 x 8" (203mm) Polycellulose Low-Frequency Woofer

New High Definition Imaging (HDI) Waveguide

1" (25mm) Aluminum Dome Tweeter

Recommended Amplifier Power: 20 – 225W

Frequency Response: 36Hz – 40 Sensitivity: 91dB @ 1M, 2.83V Nominal Impedance: 6 Ohms

Crossover Frequencies: 1.4kHz. 2.0kHz

Enclosure Type: Bass-Reflex via Rear-Firing Tuned Port Dimensions (W x D x H): 260 x 370 x 1070mm

Weight: 49.74 lbs (22.56kg)

STAGE A180

2.5 way, dual 6.5", 1" aluminum tweeter floor standing loudspeaker

2 x 6.5" (165mm) Polycellulose Low-Frequency Woofer

New High Definition Imaging (HDI) Waveguide

1" (25mm) Aluminum Dome Tweeter

Recommended Amplifier Power: 20 – 225W

Frequency Response: 40Hz – 40kHz Sensitivity: 90dB @ 1M, 2.83V Nominal Impedance: 6 0hms

Crossover Frequencies: 1.4kHz, 2.2kHz

Enclosure Type: Bass-Reflex via Rear-Firing Tuned Port

Dimensions (W x D x H): 230 x 295 x 1000mm

Weight: 38.03 lbs (17.25kg)

STAGE A170

2.5 way, dual 5.25", 1" aluminum tweeter floor standing loudspeaker

2 x 5.25" (133mm) Polycellulose Low-Frequency Woofer

New High Definition Imaging (HDI) Waveguide

1" (25mm) Aluminum Dome Tweeter

Recommended Amplifier Power: 20 – 200W

Frequency Response: 44Hz – 40 Sensitivity: 89dB @ 1M, 2.83V Nominal Impedance: 6 Ohms

Crossover Frequencies: 1.8kHz. 2.8kHz

Enclosure Type: Bass-Reflex via Rear-Firing Tuned Port

Dimensions (W x D x H): 190 x 255 x 930mm

Weight: 31.61 lbs (14.34kg)

STAGE A130

2 way, 5.25" woofer, 1" aluminum tweeter bookshelf loudspeakers

5.25" (133mm) Polycellulose Low-Frequency Woofer

New High Definition Imaging (HDI) Waveguide

1" (25mm) Aluminum Dome Tweeter

Recommended Amplifier Power: 20 – 125W

Frequency Response: 55Hz – 40kHz Sensitivity: 86dB @ 1M, 2.83V Nominal Impedance: 6 0hms Crossover Frequencies: 3.2kHz

Enclosure Type: Bass-Reflex via Rear-Firing Tuned Port

Dimensions (W x D x H): 190 x 230 x 321mm

Weight (each): 12.02 lbs (5.45kg)

STAGE A120

2 way, 4.5" woofer, 1" aluminum tweeter bookshelf/surround loudspeakers

4.5" (114mm) Polycellulose Low-Frequency Woofer

New High Definition Imaging (HDI) Waveguide

1" (25mm) Aluminum Dome Tweeter

Recommended Amplifier Power: 20 – 125W

Frequency Response: 60Hz – 40kHz Sensitivity: 86dB @ 1M, 2.83V Nominal Impedance: 6 0hms Crossover Frequencies: 3.2kHz

Enclosure Type: Bass-Reflex via Rear-Firing Tuned Port

Dimensions (W x D x H): 170 x 170 x 285mm

Weight (each): 8.40 lbs (3.81kg)

STAGE A135C

2 way, 6 x 3" woofer, 1" aluminum tweeter center loudspeaker

6 x 3" (76mm) Polycellulose Low-Frequency Woofer New High Definition Imaging (HDI) Waveguide

1" (25mm) Aluminum Dome Tweeter

Recommended Amplifier Power: 20 – 150W

Frequency Response: 75Hz – 40kHz Sensitivity: 90dB @ 1M, 2.83V Nominal Impedance: 6 0hms Crossover Frequencies: 2.5kHz

Enclosure Type: Bass-Reflex via Side-Firing Tuned Ports

Dimensions (W x D x H): 745 x 166 x 104mm

Weight: 16.42 lbs (7.45kg)



Home Audio Loudspeaker System



STAGE A125C

2 way, dual 5.25" woofer, 1" aluminum tweeter center loudspeaker

Dual 5.25" (133mm) Polycellulose Low-Frequency Woofer

New High Defi nition Imaging (HDI) Waveguide

1" (25mm) Aluminum Dome Tweeter

Recommended Amplifi er Power: 20 – 150W

Frequency Response: 75Hz – 40kHz Sensitivity: 88dB @ 1M, 2.83V Nominal Impedance: 6 0hms Crossover Frequencies: 2.6kHz

Enclosure Type: Sealed

Dimensions (W x D x H): 469 x 220 x 190mm

Weight: 17.53 lbs (7.95kg)

STAGE SUB A120P

12" 500 Watts powered subwoofer

12" (305mm) Polycellulose Low-Frequency Woofer

Power: 250W RMS (500W Dynamic) Frequency Response: 32Hz – 150Hz

Crossover Frequencies: 50Hz – 150Hz (variable) 24dB/octave

Controls: Auto Power, Crossover, Level, Phase

Input: 1 x Line-Level LFE Input

Enclosure Type: Bass-Refl ex via Rear-Firing Tuned Ports Power Requirement: 120V, 60Hz (US) 220-230V, 50/60Hz (EU)

Power Consumption (Idle/Full/Power): <0.5W (standby) / 335W/2A (max

– 230V) / 335W/4A (max – 120V) Dimensions (W x D x H): 390 x 420 x 395mm

Weight: 41.09 lbs (18.64kg)

STAGE SUB A100P

10" 300 Watts powered subwoofer

10" (250mm) Polycellulose Low-Frequency Woofer

Power: 150W RMS (300W Dynamic) Frequency Response: 35Hz – 150Hz

Crossover Frequencies: 50Hz – 150Hz (variable) 24dB/octave

Controls: Auto Power, Crossover, Level, Phase

Input: One (1) Line-Level LFE Input

Enclosure Type: Bass-Refl ex via Rear-Firing Tuned Ports
Power Requirement: 120V, 60Hz (US) 220-230V, 50/60Hz (EU)
Power Consumption (Idle/Full/Power): <0.5W (standby) / 205W/1.6A

(max – 230V) / 205W/3.15A (max – 120V) Dimensions (W x D x H): 335 x 380 x 340mm

Weight: 30.05 lbs (13.63kg)

